


## **SPECIFICATIONS**

Size	Metric	British
Max. Working Height(Inside)	14.30m	46ft 11in
Max. Working Height(Outside)	14.30m	46ft 11in
Max. Platform Height(Inside)	12.30m	40ft 4in
Max. Platform Height(Outside)	12.30m	40ft 4in
Overall Length(Without Outriggers)	3.19m	10ft 6in
Overall Length(With Outriggers) <b>©</b>	3.84m	12ft 7in
Overall Width <b>(</b>	1.76m	5ft 9in
Overall Height(Rails Up)	2.74m	9ft
Overall Height(Rails Down)	1.97m	6ft 6in
Platform Size(Length×Width)	2.88m×1.52m	9ft 5in × 5ft
Platform Extension Size <b>G</b>	1.43m	4ft 8in
Ground Clearance	0.24m	9in
Wheelbase <b>(1)</b>	2.29m	7ft 6in
Turning Radius(Inside/Outside)	2.15m/4.85m	7ft 1in/15ft 11in
Tyres	26×12-16.5	26×12-16.5

Performance		
S.W.L	363kg	800lb
S.W.L On Extension	136kg	299lb
Max. Occupants(Inside/Outside)	3/2	3/2
Gradeability	40%	40%
Travel Speed(Stowed)	6.00km/h	3.73mph
Travel Speed(Raised)	0.45km/h	0.28mph
Max. Working Slope	X-1.5°/Y-3°	X-1.5°/Y-3°
Up/Down Speed	45/46sec	45/46sec

Weight			
Overall Weight	5150kg	11353lb	

71L 48V/320Ah	18.7gal 48V/320Ah
48V/320Ah	48V/320Ah
48V/35A	48V/35A
2×32VAC/3.3kW	2×32VAC/3.3kW
48VDC/3.8kW	48VDC/3.8kW
2	2×32VAC/3.3kW



ANSI A92.20, CSA B354.6.17



Self-propelled Scissor Lifts



## **FEATURES**

## Standard Items

- Proportional Joystick Controls
- Self-Locking Gates
- One-Way Platform Extension Deck
- Two-Wheel Drive
- Two-Wheel Steering
- Automatic Braking System
- Emergency Descent System
- Tubing Explosion-Proof System
- Onboard Fault Diagnostic System
- Tilt Alarm
- Motion Alarm
- Horn
- Hour Meter
- Charging Protection System
- Flashing LED Beacon
- Foldable Guard Rails
- Drive Enable
- Charging Indicator
- Manual Brake Release
- · Lanyard Attachment Point
- Standard Transport Forklift Pockets
- Tie-Down And Lifting Points
- Automatic Leveling Hydraulic Outriggers
- Emergency Stop Button
- Platform Load Sense System
- Drivable At Full Height
- Oscillating Axle Chassis



## ZHEJIANG DINGLI MACHINERY CO., LTD.

Address: No.188 Qihang Road, Deqing, Zhejiang P.R.C 313219

Telephone: +86(572)8681688 E-Mail: export@cndingli.com Https://en.cndingli.com









